

DL/DM Series

DL-DM SERIES

Pole setting sheave height of 19.8 m

Side reach of 17 m

Digging radius up to 11.9 m

Altec optiView® control seat

Altec Electronic Side-Load Protection System

Altec-Opti-View Control Seat



1300 1ALTEC
www.altecaus.com.au



STANDARD FEATURES

- Hydraulically extending full capacity fibreglass upper boom
- Continuous rotation with high capacity worm drive gearbox
- Outrigger controls with motion alarms and tool circuit at tailshelf
- Operator main control panel with multi-lever controls
- Emergency stop switch on main control panel(s)
- Five function Hydraulic Overload Protection system
- Hydraulic side load and boom storage protection systems
- 15,000 lbs capacity turntable winch with rope/cable guides
- Fibreglass boom tip and transferable steel flares for pole setting
- Hydraulically tilting pole guides with pole guide interlock
- Insulated per ANSI "46kV and below" dielectric rating
- Altec proportional control system
- Painted white with Altec Powder Coat Paint process
- Designed and manufactured in facilities certified to ISO 9001

OPTIONS

- Behind cab and corber mount
- Boom tip winch
- High speed (12,000 lbs) winch
- Traditional control seat
- Altec Opti-View control seat
- Engine foot throttle
- Control and platform covers
- Radio remote main control panel
- Radio remote upper controls platform
- Altec RotaFloat
- Hydraulic upper controls
- Altec electronic side load protection

RECOMMENDED OPTIONS

- Fall protection system
- Wheel chocks
- Outrigger pads
- Platform cover
- Platform scuff pads

GENERAL SPECIFICATIONS

	DM45	DM47	DL42	DL45
Maximum Lift Capacity	13,608 kg	13,608 kg	13,608 kg	13,608 kg
Maximum capacity at 10' radius	5883 kg	5597 kg	4663 kg	4468 kg
Pole setting sheave height	13.5 m	14.2 m	12.6 m	13.5 m
Reach from centreline of rotation	10.6 m	11.3 m	9.6 m	10.5 m
Dig radius from centreline of rotation				
Minimum	4.8 m	5.5 m	4.3 m	4.8 m
Maximum	7.5 m	8.1 m	6.5 m	7.4 m
Boom articulation	-20° to 80°	-20° to 80°	-18° to 84°	-18° to 84°
Rotation	Continuous	Continuous	Continuous	Continuous
Travel height, approximate*	3.6 m	3.6 m	3.6 m	3.6 m

*Varies Depending on Chassis Frame Height



Altec OptiView® Control Seat



Radio Remote Control



For more complete information on Altec products and services, visit us on www.altecaus.com.au. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2015 Altec Inc. All Rights Reserved. AAH.BR.AL16.7

